

SOLAR 340 LCV

Operating Weight: 33.600 ~ 34.900 kg

Bucket capacity (SAE): 1,25 ~ 1,83 m³

Engine Power: 184 kW (247 Hp) / 1.900 rpm





www.eurodaewoo.com

DAEWOO

Performance


This hydraulic excavator is equipped with the air-to-air intercooler engine, which has the greatest power output in its class and excellent fuel economy. It assures outstanding workability, productivity, and efficiency through the e-EPOS system, the new and improved version of EPOS System. This will assure increase in operating capacity and decrease in fuel consumption.



Improved manoeuvrability and control

New technologically advanced control valve and joystick valves have been installed to allow speedy, smooth and responsive control.

Advanced hydraulic circuit separates the oil flow for travel and boom function to allow precise and safe operation when handling loads during travel.



The circuits for the boom, arm, and bucket have been improved to assure smooth and confident control during combination.

Air-to-Air Intercooler Engine

Greatest power output and high-efficiency engine in its class.

Environmentally friendly, Green engine

This machine is equipped with the engine meeting the U.S. EPA Tier-II Regulations and European stage-II.

Increased swing force. (Equipped with antirebound valve)

Swing torque has been increased by 14% to improve turning acceleration and deceleration and antirebound valve is installed as standard equipment, which allows the operator to stop the upper structure at the desired position. As a result, operating efficiency has been greatly improved.

Joystick grip with 3 switches

Spare switches are installed on both joystick grips to control the additional attachment.



Excellent Reliability

Daewoo's world-class center for product reliability performs sophisticated testing on all completed products, to ensure they meet or exceed market standards.



Heat shield panel for turbo charger

The heat shield guard has been installed over the turbo charger to prevent the operator from inadvertently touching the hot surfaces while checking the engine area.

Brushless type alternator

The semi-permanent alternator, resistant to dust and other pollutants for heavy-duty applications has been installed.

Emergency throttle cable

In the event of engine speed control dial malfunction, emergency throttle cable mounted in the cabin can be used to manually control engine speed.

Improved stability

The center of gravity has been lowered and optimized by the strengthened undercarriage and heavier counter weight. These have greatly improved the dynamic stability and side lifting capacity.



360° fan guard

A metal mesh guard has been installed all around the fan blade to prevent accidental bodily injury.

Larger rubber pipe clamps

Larger size and improved material pipe clamps have been installed. This has resulted in noise reduction, increased vibration absorption and durability characteristics as well as preventing pipe cracks.


Rubber coated wire harness clamps

Electric wire harnesses have been mounted with rubber coated clamps to decrease vibration damage.



Working Environment

Wide operator cabin space meeting the ISO Standards and expanded all-round visibility. The low-noise, low-vibration type comfortable cabin provides the operator with safe and ergonomic operating environment.



Good visibility

The enlarged right-hand glass and the minimized crosswise strut in wind-shield have been achieved to increase the visual range by 15% when compared to the previous machine.

Increased foot space

Instruments, controls, and accessories have been ergonomically located in the cabin and 300mm seat slide has been achieved to provide ample space for operator's feet and legs.





Fresh Air Type Air Conditioner

One touch selector switch for the air conditioner and heater output, featuring a multivent circulation system that allows for greater cooling / heating performance. Improved front window defroster system has been added to provide enhanced clarity and visibility during any working condition.

- Easy replaceable air filter
- Larger cool air intake vents
- Industry standard fresh air/recirculation control system incorporated
- Modular electric fan condenser compartment



Cup holder


A folding style cup holder has been installed in the cabin allowing the operator to easily store a can or cup.

12 V Spare Power Socket

This socket can be used for charging a cellular phone or powering a small 12V DC electrical device.

Low Vibration Cab Mounting System

By using a total isolating seal design (full sealing) outside noise has been drastically reduced to the levels comparable to that in a modern car. A viscous sealed mounting system has been incorporated, and the frame, cabin and seat have been designed to absorb major and minor vibrations, resulting in a significant decrease in vibration felt by the operator.



Long wind shield wiper blade

Front visibility is further improved by using the lengthened wiper blade.


Large ceiling cover

The ceiling cover can be opened to confirm the bucket operation even at the maximum excavating height.



Maintenance

Quick and easy service checks, maximizing the excavator's life expectancy.



Engine oil drain valve


The engine oil drain valve with quick coupler provides fast and environmentally sound serviceability.

Electrical control access box

Pull-out style drawer for electrical control access box allows for easy service and maintenance.

PC monitoring function (SMS)

By connecting a laptop PC to the controller (e-EPOS controller) of the machine, data such as pump pressure and engine RPM can be displayed graphically. Also other various machine status data can be stored in memory and printed out using a printer.



Easy installation for the 3rd pump

The PTO mountable pump has been installed permitting easy mounting of the 3rd pump.

Easy radiator cleaning

The clearance between the oil cooler and radiator has been widened for easy insertion of the air nozzle during cleaning.

Water separator

The transparent glass water separator is mounted at a location easily accessible from the ground allowing easy maintenance of the fuel system.



GRAPHIC DISPLAY LCD MONITOR PANEL

The information monitor panel displays both text and symbols for easy recognition of machine status and various other data.

SIMPLIFIED OPERATION MODE

SELECTION


The 3 work modes from the previous models have been reduced to digging and trenching modes for easy selection.

Digging Mode :

General Excavating, Ground Leveling, Loading Dump Truck, allows for versatility.

Trenching Mode :

trenching or excavating of side wall, operations which require heavy swing work.



Self-diagnosis and fault history memory functions

Current faults and past faults history of the excavator control system are displayed and memorized on a real-time basis to enable correct diagnosis and quick repair.


Real-time clock with day / date

The real-time clock displays date and day in easy to read format.



Filter / oil operating hour display

The hours in use for 9 filters and oils can be displayed so that replacement intervals can be easily recognized.



Multiple language display

The user menu can be displayed in multiple languages for the operator's convenience.

Real-time machine data display

Displays 28 different machine status data and information such as pump delivery pressure and engine RPM.



Technical Data

ENGINE

MODEL

DAEWOO DE12TIS

TYPE

Water-cooled, 4-cycle, direct injection

ASPIRATION

Turbocharged – Air-to-Air intercooler

NUMBER OF CYLINDERS

6

RATED FLYWHEEL HORSE POWER

DIN 6271, net	184 kW (250 Ps)
	at 1.900 rpm
SAE J1349, net	184 kW (247 Hp)
	at 1.900 rpm

PISTON DISPLACEMENT

11.051 cc

MAXIMUM TORQUE

108 kgf.m (1.059 Nm) at 1.400 rpm

BORE AND STROKE

123 x 155 mm

STARTING SYSTEM

24 V electric motor

BATTERIES

2 x 12 V x 150 Ah

e-EPOS (Electronic Power Optimizing System) allows the operator to maximize work efficiency over a full range of operating conditions and to minimize fuel consumption.

- Hydraulic system assures fully independent and combined operations.
- Automatic 2 speed travel system for high traction force and travel speed.
- Cross-sensing and fuel saving pump system.
- Auto idle system.
- 2-Working /2-power mode selection system.
- Computer aided engine-pump control.

MAIN PUMPS

2 variable displacement axial piston pumps.

Max. oil flow 2 x 262 l/min

PILOT PUMP

Gear pump

Max. oil flow 22,5 l/min

SWING MOTOR

Relief valve 266 bar

MAIN RELIEF VALVES

Boom/Arm/Bucket

– Normal 324 bar

– Power Boost 343 bar

Travel circuit 324 bar

High-strength piston rods and tubes are used. Cylinder cushion mechanism is provided for all cylinders to assure shock-free operation and extend life of cylinder.

Cylinders	Q'ty	Bore x Rod dia. x Stroke
Boom	2	150 x 100 x 1.440 mm
Arm	1	170 x 115 x 1.812 mm
Bucket	1	150 x 100 x 1.300 mm

SUPER-STRUCTURE REVOLVING FRAME

A deep, full-reinforced box section. Heavy-gauge steel plates used for ruggedness.

2 TRAVEL PEDALS WITH LEVERS

Pilot pressure control type. Independent drive at each track allows counter-rotation of the tracks. Levers are detachable.

CONTROLS 2 IMPLEMENT LEVERS

Pilot pressure control type. Right lever is boom and bucket control, left lever for swing and arm control.

OPERATOR'S CAB


A roomy, independent, shock and noise-free operator's cab, 4 side safety glass windows give all-round visibility. Front window slides up and stores in the roof and side window can be opened for ventilation. Fully adjustable suspension seat. Air conditioner. ISO standard cab.

NOISE LEVELS (DYNAMIC VALUE)
LwA external noise:

- Guaranteed Sound Power Level 107 dB (A) (2000/14/EC)
- Measured Sound Power Level 106 dB (A) (2000/14/EC)

LpA operator noise:

76 dB (A) (ISO 6396)





SWING MECHANISM



DRIVE



UNDERCARRIAGE

High-torque, axial piston motor with planetary reduction gear bathed in oil. Swing circle is singlerow, shear type ball bearing with induction-hardened internal gear. Internal gear and pinion gear immersed in lubricant. Swing parking brake is spring-set, hydraulic-released disc type. A two position swing lock secures the super-structure for transportation.

SWING SPEED

0 to 8,9 rpm

REAR SWING RADIUS

3.500 mm

Each track is driven by an independent, high-torque, axial piston motor through planetary reduction gear. Two levers or foot pedal control provide smooth travel or counter-rotation upon demand.

TRAVEL SPEED

4,6/3,1 km/h

MAXIMUM TRACTIVE FORCE

Force 27.800 kgf

Gradeability 35° (70%) continuous

Tractor type undercarriage. Heavy-duty track frame, all welded stress-relieved structure. Top grade materials are used for toughness. Side frames are welded, securely and rigidly, to the track frame.

Lifetime-lubricated track rollers, idlers and sprockets with floating seals. Track shoes of induction-hardened rolled alloy with triple grousers. Specially heart-treated connecting pins. Hydraulic track adjusters with shock-absorbing recoil springs.

NUMBER OF ROLLERS AND SHOES

(EACH SIDE) GROUND CONTACT AREA

Upper rollers 2

(STANDARD SHOE)

Lower rollers 9

Track shoes 51

Overall track length 4.960 mm



BRAKE



WEIGHT

Two oil disc brake on final drive input shafts. Parking brake is spring-set, hydraulic-released disc type.

Equipped with 6,5 m boom, 3,2 m arm, and 1,48 m³ (SAE heaped) bucket and 600 mm shoes.

SHOE TYPE	Shoe Width	Operating weight	Ground pressure
Triple grouser	600 mm	33.900 kg	0,65 kgf/cm ²
	700 mm	34.300 kg	0,56 kgf/cm ²
	800 mm	34.700 kg	0,50 kgf/cm ²
	850 mm	34.900 kg	0,47 kgf/cm ²



SERVICE REFILL CAPACITIES (liters)

Fuel tank 550

Cooling system 58

LUBRICATION

Engine oil 28

Swing drive (each) 6

Final drive (each) 5,5

Hydraulic system 460

Hydraulic tank 390



BUCKETS

SAE, heaped	CECE, heaped	CAPACITY		WIDTH	WEIGHT	RECOMMENDATION		
		Without side cutters	With side cutters			2,6 m Arm	3,2 m Arm	4,0 m Arm
1,25 m ³	1,1 m ³	1.228 mm	1.273 mm	1.233 kg	A	A	B	
1,48 m ³	1,3 m ³	1.410 mm	1.456 mm	1.340 kg	A	B	B	
1,61 m ³	1,4 m ³	1.500 mm	1.546 mm	1.399 kg	A	B	B	
1,83 m ³	1,6 m ³	1.678 mm	1.723 mm	1.514 kg	A	B	C	


A. Suitable for materials with density of 2.000 kg/m³ or less

B. Suitable for materials with density of 1.600 kg/m³ or less

C. Suitable for materials with density of 1.100 kg/m³ or less


Dimensions & Working Ranges

DIMENSIONS



	S340LCV	S340NLCV
A Overall width of upper structure	2.990 mm	2.990 mm
B Overall width of cab	960 mm	960 mm
C Overall height of cab	3.080 mm	3.080 mm
D Tail swing radius	3.500 mm	3.500 mm
E Overall height of boom		
Arm length (3,2 m)	3.550 mm	3.550 mm
Arm length (2,6 m)	3.600 mm	3.600 mm
Arm length (4,0 m)	3.990 mm	3.990 mm
F Clearance under counterweight	1.195 mm	1.195 mm
G Ground clearance	506 mm	506 mm
H Tumbler distance	4.010 mm	4.010 mm
I Track length	4.960 mm	4.960 mm
J Track gauge	2.680 mm	2.400 mm
K Track shoe width	600 mm	600 mm
L Overall length		
Arm length (3,2 m)	11.330 mm	11.330 mm
Arm length (2,6 m)	11.425 mm	11.425 mm
Arm length (4,0 m)	11.340 mm	11.340 mm
M Overall track width	3.280 mm	3.000 mm

WORKING RANGES



DIGGING FORCES (ISO)

	3,2 m	2,6 m	4,0 m
Bucket digging force *	kgf 24.500 KN 240	kgf 24.500 KN 240	kgf 24.500 KN 240
Arm digging force *	kgf 17.900 KN 176	kgf 21.900 KN 215	kgf 15.300 KN 150


* At power boost

Boom length (6,5 m)

Arm length	3.200 mm	2.600 mm	4.000 mm
A. Max. digging reach	11.230 mm	10.620 mm	11.990 mm
B. Max. digging reach at ground level	11.040 mm	10.420 mm	11.810 mm
C. Max. digging depth	7.670 mm	7.070 mm	8.480 mm
D. Max. digging height	10.440 mm	10.010 mm	10.820 mm
E. Max. dumping height	7.270 mm	6.890 mm	7.640 mm
F. Max. vertical wall digging depth	6.200 mm	5.320 mm	6.990 mm
G. Max. digging depth (2,44 m level)	7.510 mm	6.860 mm	8.340 mm

Lifting Capacities

STANDARD



Boom : 6,5 m

Arm : 3,2 m

Bucket : SAE 1,48 m³ (CECE 1,3 m³)

Shoe : 600 mm

Unit : 1.000 kg

Standard Track

A(m)	2	3	4	5	6	7	8	9	Max. Reach
B(m)	7								A(m)
7							*6,11	*6,11	
6							*6,24	6,06	
5						*6,88	*6,88	*6,56	5,96
4				*9,69	*9,69	*8,39	*8,39	*7,56	7,28
3			*14,97	*14,97	*11,47	*11,47	*9,52	9,01	*8,30
2					*17,56	16,24	*10,60	8,69	*9,04
1					*16,12	15,72	*14,36	11,10	*11,51
0		*8,24	*8,24	*16,30	15,47	*15,14	10,86	*12,16	8,24
-1	*8,21	*8,21	*11,38	*11,38	*18,51	15,39	*15,46	10,73	*12,51
-2	*11,59	*11,59	*14,89	*14,89	*19,40	15,40	*15,36	10,70	*12,54
-3	*15,13	*15,13	*18,93	*18,93	*18,52	15,50	*14,86	10,73	*12,22
-4	*19,11	*19,11	*21,77	*21,77	*17,13	15,67	*13,89	10,84	*11,46
-5	*23,82	*23,82	*18,86	*18,86	*15,06	*15,06	*12,29	11,02	*10,05
-6			*14,71	*14,71	*11,92	*11,92	*9,59	*9,59	



Note 1. Ratings are based on SAE J1097

2. Load point is the hook on the back of the bucket


3. * = Rated loads are based on hydraulic capacity

4. Rated loads do not exceed 87% of hydraulic capacity or 75% of tipping capacity

□ : Rating over front

□○ : Rating over side or 360 degree

○ : Ground



OPTION

Boom : 6,5 m
Arm : 2,6 m
Bucket : SAE 1,83 m³ (CECE 1,6 m³)
Shoe : 600 mm
Unit : 1.000 kg

Narrow Track

A(m)	2	3	4	5	6	7	8	9	Max. Reach	A(m)	
B(m)	7						*6,53	*6,53			
6							*6,81	6,48	*6,64	5,07	
5						*7,96	*7,96	*7,30	6,33	*6,89	5,00
4				*13,57	*13,57	*10,60	10,59	*8,96	7,92	*7,93	6,15
3				*16,59	14,12	*12,30	10,08	*10,02	7,61	*8,62	5,95
2				*14,40	13,44	*13,75	9,64	*10,99	7,33	*9,28	5,77
1				*13,65	13,14	*14,73	9,35	*11,75	7,11	*9,82	5,62
0				*16,14	13,05	*15,21	9,19	*12,22	6,97	10,05	5,51
-1				*12,47	*12,47	*19,27	13,06	*15,24	9,13	*12,38	6,90
-2	*14,07	*14,07		*17,50	*17,50	*18,52	13,14	*14,89	9,14	*12,20	6,89
-3	*18,79	*18,79		*21,65	*21,65	*17,34	13,27	*14,11	9,22	*11,64	6,94
-4	*24,14	*24,14		*19,28	*19,28	*15,61	13,48	*12,81	9,37	*10,54	7,06
-5				*15,90	*15,90	*13,05	*13,05	*10,68	9,61		

A(m)	2	3	4	5	6	7	8	9	10	Max. Reach	A(m)	
B(m)	Boom : 6,5 m – Arm : 4,0 m – Bucket : SAE 1,25 m³ (CECE 1,1 m³) – Shoe : 600 mm											
8										*4,84	*4,84	
7										*4,81	*4,81	
6										*4,85	4,40	
5										*4,95	4,06	
4										*5,11	3,83	
3										*5,33	3,68	
2										*5,53	10,44	
1										*5,62	3,59	
0										*5,67	10,43	
-1										*5,70	3,62	
-2										*5,70	10,02	
-3										*5,74	9,66	
-4										*5,75	9,16	
-5										*5,77	8,53	
-6										*5,79	7,70	
-7										*5,82	6,62	
										*5,84	5,13	

A(m)	2	3	4	5	6	7	8	9	Max. Reach	A(m)	
B(m)	Boom : 6,5 m – Arm : 3,2 m – Bucket : SAE 1,48 m³ (CECE 1,3 m³) – Shoe : 800 mm										
7									*6,13	5,81	
6									*6,21	5,15	
5									*6,24	8,84	
4									*6,37	4,71	
3									*6,37	9,23	
2									*6,51	4,41	
1									*6,57	9,50	
0									*6,62	4,22	
-1									*6,65	9,65	
-2									*6,67	9,70	
-3									*6,69	4,13	
-4									*6,71	9,64	
-5									*6,74	4,11	
-6									*6,76	9,64	
									*6,77	9,53	

Note 1. Ratings are based on SAE J1097

2. Load point is the hook on the back of the bucket

3. * = Rated loads are based on hydraulic capacity

4. Rated loads do not exceed 87% of hydraulic capacity or 75% of tipping capacity

□ : Rating over front

□□ : Rating over side or 360 degree

○ : Ground

Standard & Optional Equipment

STANDARD EQUIPMENT

HYDRAULIC SYSTEM

- Boom and arm flow regeneration
- Boom and arm holding valves
- Swing anti-rebound valves
- Spare ports (valve)
- One-touch power boost
- Piping for hammer (one way)

CABIN & INTERIOR

- Viscous cab mounts
- All weather sound suppressed type cab
- Air conditioner
- Adjustable suspension seat with head rest and adjustable arm rest
- Pull-up type front window and removable lower front window
- Room light
- Intermittent windshield wiper
- Cigarette lighter and ashtray
- Cup holder
- Hot & cool box
- Graphic display monitor
- Fuel control dial
- AM/FM Radio and cassette player
- Remote radio ON/OFF switch
- 12V spare power socket
- Serial communication port for laptop PC interface
- Joystick lever with 3 switches

SAFETY

- Large handrails and step
- Punched metal anti-slip plates
- Seat belt
- Hydraulic safety lock lever
- Safety glass
- Hammer for emergency escape
- Right and left rearview mirrors
- Boom and arm hose rupture protection valve

OTHERS

- Double element air cleaner
- Pre-cleaner
- Water separator
- Dust screen for radiator
- Engine overheat prevention system
- Engine restart prevention system
- Self-diagnostic system
- Alternator (24 V, 50 A)
- Electric horn
- Halogen working lights (frame mounted 2, boom mounted 2)
- Electric fuel supply pump
- Hydraulic track adjuster
- Track guards

OPTIONAL EQUIPMENT

SAFETY

- Overload warning device
- Cabin Top/Front guard (FOGS standard)
- Travel alarm
- Travel & swing alarm
- Rotating beacon

CABIN & INTERIOR

- Sunvisor
- Sun roof

OTHERS

- Piping for rotation
- Double fuel filter
- Additional work lights on the cabin
 - 2 front lamps
 - 4 front and 2 rear lamps
- Large capacity alternator (24 V, 80 A)

Boom and arm hose rupture protection valve




Sunvisor



Additional work lights on the cabin



Electric fuel supply pump



Rotating beacon



SOLAR 340 LCV

Seoul Office

9th Floor, Daewoo Heavy Industries & Machinery Ltd. Bldg.
14-34, Youido-dong, Youngdungpo-gu
150-010, Seoul Korea
Mail: C. P. O Box 7955 Seoul, Korea
Tel. +82 2 2167-3114 Fax +82 2 785-2677
Website: www.dhiltc.co.kr

Euro Daewoo S. A.

1A Rue Achille Degrâce,
7080 Frameries, Belgium
Tel. +32 65 61 32 30 Fax +32 65 67 73 38

Euro Daewoo France

2/4, Rue Pavlov, Z.I. des Bruyères
78190 Trappes, France
Tel. +33 1 30 16 21 41 Fax +33 1 30 16 21 44

Euro Daewoo UK

Daewoo House Unit 6.3 Nantgarw Park Cardiff
CF4 7QU, U.K.
Tel. +44 1443 842273 Fax +44 1443 841933

Daewoo Maschinen Vertriebs GmbH

Hans-Böckler-Str. 27-29
40764 Langenfeld, Germany
Tel. +49 2173 8509 18 Fax +49 2173 8509 40
Website: www.daewoomaschinen.de

The illustrations do not necessarily show the product in standard version. All products and equipments are not available in all markets.
Materials and specifications are subject to change without prior notice.

S340LCV_UK_02/05 • Design by Site Communication (Belgium)

www.eurodaewoo.com

DAEWOO